

Package: wheatmap (via r-universe)

October 18, 2026

Type Package

Title Incrementally Build Complex Plots using Natural Semantics

Version 0.2.4

URL <https://github.com/zwdzwd/wheatmap>

BugReports <https://github.com/zwdzwd/wheatmap/issues>

Description Builds complex plots, heatmaps in particular, using natural semantics. Bigger plots can be assembled using directives such as 'LeftOf', 'RightOf', 'TopOf', and 'Beneath' and more. Other features include clustering, dendrograms and integration with 'ggplot2' generated grid objects. This package is particularly designed for bioinformaticians to assemble complex plots for publication.

Encoding UTF-8

License GPL-3

RoxygenNote 7.3.3

Imports grid, gtable, stats, colorspace, RColorBrewer, pals

Suggests knitr, rmarkdown, png, testthat (>= 3.0.0)

Config/testthat/edition 3

VignetteBuilder knitr

Language en-US

Repository <https://zwdzwd.r-universe.dev>

Date/Publication 2026-06-03 18:19:18 UTC

RemoteUrl <https://github.com/zwdzwd/wheatmap>

RemoteRef HEAD

RemoteSha bdd14bb4516f93d60ad4dac9df3f3635ca78d9d4

Contents

[.WGroup	3
+.WObject	3
AddWGroup	4
Beneath	4
both.cluster	5
BottomLeftOf	6
BottomRightOf	7
CalcTextBounding	7
CalcTextBounding.WHeatmap	8
CMPar	9
ColorMap	10
column.cluster	11
FromAffine	11
getdim	12
grid.dendrogram	12
GroupCheckNameUnique	13
GroupDeepGet	13
LeftOf	14
ly	15
MapToContinuousColors	15
MapToDiscreteColors	16
print.WDendrogram	16
print.WGenerator	17
print.WGG	17
print.WGrob	18
print.WGroup	18
print.WHeatmap	19
print.WLabel	20
print.WRect	20
Resolve	21
RightOf	21
row.cluster	22
ScaleGroup	23
ToAffine	23
TopLeftOf	24
TopOf	24
TopRightOf	25
WColorBarH	26
WColorBarV	27
WColumnBind	28
WCustomize	29
WDendrogram	30
WDim	31
WGG	32
WGrob	32
WGroup	33

<i>[.WGroup</i>	3
-----------------	---

WHeatmap	34
WLabel	36
WLegendH	37
WLegendV	38
WMatrix	39
WObject	39
WPosition	40
WRect	41
WRowBind	41

Index	43
--------------	-----------

<i>[.WGroup</i>	<i>subset WGroup</i>
-----------------	----------------------

Description

subset WGroup

Usage

```
## S3 method for class 'WGroup'  
x[i]
```

Arguments

- x a WGroup object
- i integer indexing element

Value

a subset of WGroup or NULL

<i>+.WObject</i>	<i>merge plotting objects</i>
------------------	-------------------------------

Description

merge plotting objects

Usage

```
## S3 method for class 'WObject'  
group + p
```

Arguments

group	a WGroup or a plotting object
p	a new plotting object

Value

a WGroup

AddWGroup	<i>Add a plotting object to a group</i>
-----------	---

Description

The object to be added are in the same coordinate system as the group.

Usage

```
AddWGroup(group.obj, new.obj)
```

Arguments

group.obj	WGroup object to be added to
new.obj	plotting object to be added

Value

a WGroup object where new.obj is added.

Beneath	<i>Beneath</i>
---------	----------------

Description

Generate dimension beneath another object. Tags the result with ‘placement = "south"’; see [TopOf()] for what that controls.

Usage

```
Beneath(
  x = NULL,
  height = NULL,
  pad = 0.01,
  min.ratio = 0.02,
  h.aln = NULL,
  v.scale = NULL,
  v.scale.proportional = FALSE
)
```

Arguments

x	an object with dimension
height	the height of the new object (when NULL set proportional to the data)
pad	padding between the target and current
min.ratio	minimum ratio of dimensions when auto-scale
h.aln	object for horizontal alignment (when NULL, set to x)
v.scale	object for vertical scaling (when NULL, set to x)
v.scale.proportional	when v.scale is provided, whether to make proportional to data

Value

a dimension generator beneath x (with 'placement = "south"')

Examples

```
WHeatmap(matrix(rnorm(2000),nrow=40)) +
  WColorBarH(1:20, cmp=CMPar(), continuous=FALSE, Beneath())
```

both.cluster	<i>row- and column-cluster a matrix</i>
--------------	---

Description

row- and column-cluster a matrix

Usage

```
both.cluster(
  mat,
  extra.row = NULL,
  extra.column = NULL,
  hc.method = "ward.D2",
  dist.method = "euclidean"
)
```

Arguments

mat	input matrix
extra.row	extra row reordering
extra.column	extra column reordering
hc.method	method to use in hclust
dist.method	method to use in dist

Value

a list of clustered row, column and matrix

Examples

```
WHeatmap(both.cluster(matrix(rnorm(100),nrow=10))$mat)
```

BottomLeftOf	<i>Bottom left of</i>
--------------	-----------------------

Description

Place a new object to the bottom left corner of another.

Usage

```
BottomLeftOf(x = NULL, just = c("right", "bottom"), v.pad = 0, h.pad = 0)
```

Arguments

x	target object, either a name, a object or NULL which refers to the last plotting object
just	the part from the new object that should be attached to
v.pad	vertical translational padding [0.0]
h.pad	horizontal translational padding [0.0]

Value

a WDimGenerator

Examples

```
WHeatmap(matrix(rnorm(2000),nrow=40)) +
  WHeatmap(matrix(c(rnorm(100)+1,rnorm(100)), nrow=10),
    cmp=CMPar(brewer.name = 'RdGy'), BottomLeftOf(just=c('right','top'))))

WHeatmap(matrix(rnorm(2000),nrow=40)) +
  WHeatmap(matrix(c(rnorm(100)+1,rnorm(100)), nrow=10),
    cmp=CMPar(brewer.name = 'RdGy'), BottomLeftOf(just=c('right','bottom'))))

WHeatmap(matrix(rnorm(2000),nrow=40)) +
  WHeatmap(matrix(c(rnorm(100)+1,rnorm(100)), nrow=10),
    cmp=CMPar(brewer.name = 'RdGy'), BottomLeftOf(just=c('left','bottom'))))
```

BottomRightOf	<i>Bottom right of</i>
---------------	------------------------

Description

Place a new object to the bottom right corner of another.

Usage

```
BottomRightOf(x = NULL, just = c("left", "bottom"), v.pad = 0, h.pad = 0)
```

Arguments

<code>x</code>	target object, either a name, a object or NULL which refers to the last plotting object
<code>just</code>	the part from the new object that should be attached to
<code>v.pad</code>	vertical translational padding [0.0]
<code>h.pad</code>	horizontal translational padding [0.0]

Value

a WDimGenerator

Examples

```
WHeatmap(matrix(rnorm(2000),nrow=40)) +
  WHeatmap(matrix(c(rnorm(100)+1,rnorm(100)), nrow=10),
    cmp=CMPar(brewer.name = 'RdGy'), BottomRightOf(just=c('left','top'))))

WHeatmap(matrix(rnorm(2000),nrow=40)) +
  WHeatmap(matrix(c(rnorm(100)+1,rnorm(100)), nrow=10),
    cmp=CMPar(brewer.name = 'RdGy'), BottomRightOf(just=c('left','bottom'))))

WHeatmap(matrix(rnorm(2000),nrow=40)) +
  WHeatmap(matrix(c(rnorm(100)+1,rnorm(100)), nrow=10),
    cmp=CMPar(brewer.name = 'RdGy'), BottomRightOf(just=c('right','bottom'))))
```

CalcTextBounding	<i>Calculate Text Bounding</i>
------------------	--------------------------------

Description

Calculate bounding box including texts.

Usage

```
CalcTextBounding(x, group)
```

Arguments

x	object
group	the top-level WGroup object

Details

W.R.T lower left corner of the view port in the unit of points

```
CalcTextBounding.WHeatmap
```

Calculate Texting Bounding for WHeatmap

Description

Calculate Texting Bounding for WHeatmap

Usage

```
## S3 method for class 'WHeatmap'  
CalcTextBounding(x, group)
```

Arguments

x	an object of class WHeatmap
group	an object of class WGroup

Value

an object of class WDim in coordinate points

CMPar

Color Map Parameters

Description

Create color map parameters

Usage

```
CMPar(
  dmin = NULL,
  dmax = NULL,
  brewer.name = NULL,
  brewer.n = 3,
  colorspace.name = NULL,
  colorspace.n = 2,
  cmap = NULL,
  label2color = NULL,
  use.data = FALSE,
  stop.points = NULL,
  na.color = "#C0C0C0",
  rev = FALSE,
  grey.scale = FALSE
)
```

Arguments

dmin	minimum for continuous color map
dmax	maximum for continuous color map
brewer.name	palette name for RColorbrewer
brewer.n	number of stop points in RColorBrewer for continuous color map
colorspace.name	colorspace name
colorspace.n	number of stops in colorspace palettes
cmap	customized colormap name
label2color	a named vector or list that defines label to color mapping explicitly for discrete color mapping
use.data	use data as color, data must be either common color names or hexadecimal color names
stop.points	custome stop points
na.color	color for NA values. Use NA for transparent (no plotting).
rev	reverse stop points
grey.scale	whether to use grey scale

Value

an object of class CMPar

Examples

```
WHeatmap(matrix(rnorm(2000),nrow=40)) +
  WColorBarV(1:20, cmp=CMPar(brewer.name = 'RdBu'), RightOf())
```

ColorMap	<i>Constructor for ColoMap object</i>
----------	---------------------------------------

Description

Create color maps

Usage

```
ColorMap(
  continuous = TRUE,
  colors = NULL,
  dmin = NULL,
  dmax = NULL,
  scaler = NULL,
  mapper = NULL
)
```

Arguments

- | | |
|------------|--|
| continuous | whether colormap is continuous |
| colors | colors for each data point |
| dmin | miminum in continuous color map |
| dmax | maximum in continuous color map |
| scaler | scaler function from data range to 0-1 |
| mapper | function that maps data to color |

Value

an object of class ColorMap

column.cluster	<i>column cluster a matrix</i>
----------------	--------------------------------

Description

column cluster a matrix

Usage

```
column.cluster(mat, ..., hc.method = "ward.D2", dist.method = "euclidean")
```

Arguments

mat	input matrix
...	extra color bars or matrix that needs column reordered
hc.method	method to use in hclust
dist.method	method to use in dist

Value

a list of clustered row, column and matrix

Examples

```
WHeatmap(column.cluster(matrix(rnorm(100), nrow=10))$mat)
```

FromAffine	<i>Convert from affine coordinates to absolute coordinates</i>
------------	--

Description

Convert from affine coordinates to absolute coordinates

Usage

```
FromAffine(dm.affine, dm.sys)
```

Arguments

dm.affine	dimension on affine coordinates (relative coordinates)
dm.sys	dimension of the affine system

Value

dimension on the same coordinate system

getdim	<i>Get dimensions</i>
--------	-----------------------

Description

Get dimensions

Usage

```
getdim(x)
```

Arguments

x	WDim object or a plotting object
---	----------------------------------

Value

vector of dimensions

grid.dendrogram	<i>Draw dendrogram under grid system</i>
-----------------	--

Description

The dendrogram can be rendered. A viewport is created which contains the dendrogram.

Usage

```
grid.dendrogram(
  dend,
  facing = c("bottom", "top", "left", "right"),
  max_height = NULL,
  order = c("normal", "reverse"),
  ...
)
```

Arguments

dend	a stats::dendrogram object.
facing	facing of the dendrogram.
max_height	maximum height of the dendrogram.
order	order
...	additional options

Details

-order should leaves of dendrogram be put in the normal order (1, ..., n) or reverse order (n, ..., 1)?
 -... pass to 'grid::viewport' which contains the dendrogram.

This function only plots the dendrogram without adding labels. The leaves of the dendrogram locates at `unit(c(0.5, 1.5, ...(n-0.5))/n, "npc")`.

Value

view port that plots dendrogram

`GroupCheckNameUnique` *Check whether group names are unique*

Description

Check whether group names are unique

Usage

```
GroupCheckNameUnique(group.obj)
```

Arguments

`group.obj` a WGroup

Value

TRUE or FALSE

`GroupDeepGet` *Get an plotting object from a group's descendants*

Description

Get an plotting object from a group's descendants

Usage

```
GroupDeepGet(x, nm, force.unique = TRUE)
```

Arguments

`x` a WGroup object
`nm` name
`force.unique` assume the name is unique in the descendants and get one object instead of a list

Value

if ‘force.unique==FALSE’ return a list. Otherwise, one plotting object.

LeftOf	<i>LeftOf</i>
--------	---------------

Description

Generate dimension to the left of another object. Tags the result with ‘placement = "west"’; see [TopOf()] for what that controls.

Usage

```
LeftOf(
  x = NULL,
  width = NULL,
  pad = 0.01,
  min.ratio = 0.02,
  v.aln = NULL,
  h.scale = NULL,
  h.scale.proportional = FALSE
)
```

Arguments

<code>x</code>	an object with dimension
<code>width</code>	the width of the new object (when NULL, set proportional to data)
<code>pad</code>	padding between the target and current
<code>min.ratio</code>	minimum ratio of dimensions when auto-scale
<code>v.aln</code>	object for vertical alignment (when NULL, set to x)
<code>h.scale</code>	object for horizontal scaling (when NULL, set to x)
<code>h.scale.proportional</code>	when h.scale is provided, whether to make proportional to data

Value

a dimension to the left of x (with ‘placement = "west"’)

Examples

```
WHeatmap(matrix(rnorm(2000),nrow=40)) +
  WColorBarV(1:20, cmp=CMPar(), continuous=FALSE, LeftOf())
```

ly	<i>show layout</i>
----	--------------------

Description

show layout

Usage

```
ly(x)
```

Arguments

x	plot
---	------

Examples

```
ly(
  WHeatmap(matrix(rnorm(2000),nrow=40)) +
  WHeatmap(matrix(rnorm(2000),nrow=40), cmp=CMPar(brewer.name = 'RdBu'),
    BottomRightOf(just=c('left','top'))))
```

MapToContinuousColors	<i>map data to continuous color</i>
-----------------------	-------------------------------------

Description

map data to continuous color

Usage

```
MapToContinuousColors(data, cmp = CMPar(), given.cm = NULL)
```

Arguments

data	numeric vector
cmp	an color map parameter object of class CMPar
given.cm	given colormap

Value

an object of ColorMap

Examples

```
barplot(1:10, col=MapToContinuousColors(1:10)$colors)
barplot(1:20, col=MapToContinuousColors(c(1:10,10:1))$colors)
```

MapToDiscreteColors *map data to discrete color*

Description

map data to discrete color

Usage

```
MapToDiscreteColors(data, cmp = CPar(), given.cm = NULL)
```

Arguments

data	numeric vector
cmp	an color map parameter object of class CPar
given.cm	given color map

Value

an object of ColorMap

Examples

```
pie(rep(1,6), col=MapToDiscreteColors(c(1:3,10:13))$colors)
```

print.WDendrogram *print a dendrogram*

Description

print a dendrogram

Usage

```
## S3 method for class 'WDendrogram'
print(x, stand.alone = TRUE, layout.only = FALSE, cex = 1, ...)
```

Arguments

x	a dendrogram
stand.alone	plot is stand alone
layout.only	plot layout only
cex	factor to scaling texts
...	additional options (ignored)

Value

view port that contains the plotted dendrogram

Examples

```
WDendrogram(column.cluster(matrix(1:24,nrow=4))$column.clust)
```

print.WGenerator	<i>print a WGenerator</i>
------------------	---------------------------

Description

This calls WGenerator and creates a WGroup to enclose the produced object.

Usage

```
## S3 method for class 'WGenerator'
print(x, ...)
```

Arguments

x	a WGenerator object
...	additional options

Value

the WGroup containing the plotting object

print.WGG	<i>plot WGG object</i>
-----------	------------------------

Description

plot WGG object

Usage

```
## S3 method for class 'WGG'
print(x, cex = 1, layout.only = FALSE, stand.alone = TRUE, ...)
```

Arguments

x	WGG
cex	scaling factor for text
layout.only	plot layout
stand.alone	produce a stand.alone plot
...	extra options

Value

printed ggobj object

print.WGrob	<i>plot WGrob object</i>
-------------	--------------------------

Description

plot WGrob object

Usage

```
## S3 method for class 'WGrob'
print(x, cex = 1, layout.only = FALSE, stand.alone = TRUE, ...)
```

Arguments

x	WGrob
cex	scaling factor for text
layout.only	plot layout
stand.alone	produce a stand.alone plot
...	extra options

print.WGroup	<i>Draw WGroup</i>
--------------	--------------------

Description

Draw WGroup

Usage

```
## S3 method for class 'WGroup'
print(x, stand.alone = TRUE, cex = 1, layout.only = FALSE, ...)
```

Arguments

<code>x</code>	a WGroup
<code>stand.alone</code>	to plot stand alone
<code>cex</code>	factor for scaling fonts
<code>layout.only</code>	to plot layout only
<code>...</code>	additional options

<code>print.WHeatmap</code>	<i>plot WHeatmap</i>
-----------------------------	----------------------

Description

plot WHeatmap

Usage

```
## S3 method for class 'WHeatmap'
print(x, cex = 1, layout.only = FALSE, stand.alone = TRUE, ...)
```

Arguments

<code>x</code>	a WHeatmap
<code>cex</code>	factor to scaling texts
<code>layout.only</code>	plot layout only
<code>stand.alone</code>	plot is stand alone
<code>...</code>	additional options

Value

NULL

Examples

```
print(WHeatmap(matrix(1:12, nrow=2)))
```

print.WLabel	<i>print WLabel</i>
--------------	---------------------

Description

print WLabel

Usage

```
## S3 method for class 'WLabel'
print(x, cex = 1, layout.only = FALSE, stand.alone = TRUE, ...)
```

Arguments

x	a WLabel object
cex	factor to scale text
layout.only	plot layout only
stand.alone	plot label stand alone
...	additional options

Examples

```
print(WLabel("This is a label."))
```

print.WRect	<i>print WRect</i>
-------------	--------------------

Description

print WRect

Usage

```
## S3 method for class 'WRect'
print(x, cex = 1, layout.only = FALSE, stand.alone = TRUE, ...)
```

Arguments

x	a WRect object
cex	factor for scaling text
layout.only	print layout only
stand.alone	plot WRect standalone
...	additional options

Value

the WRect object

Resolve	<i>Resolve name to object</i>
---------	-------------------------------

Description

Resolve name to object

Usage

Resolve(x, group, ...)

Arguments

- | | |
|-------|---------------------------------|
| x | the target |
| group | the parent WGroup object |
| ... | extra options passed to methods |

RightOf	<i>RightOf</i>
---------	----------------

Description

Generate dimension to the right of another object. Tags the result with ‘placement = "east"’; see [TopOf()] for what that controls.

Usage

```
RightOf(  
  x = NULL,  
  width = NULL,  
  pad = 0.01,  
  min.ratio = 0.02,  
  v.aln = NULL,  
  h.scale = NULL,  
  h.scale.proportional = FALSE  
)
```

Arguments

- x an object with dimension
- width the width of the new object (when NULL, set proportional to data)
- pad padding between the target and current
- min.ratio minimum ratio of dimensions when auto-scale
- v.aln object for vertical alignment (when NULL, set to x)
- h.scale object for horizontal scaling (when NULL, set to x)
- h.scale.proportional when h.scale is provided, whether to make proportional to data

Value

a dimension to the right of x (with ‘placement = "east"‘)

Examples

```
WHeatmap(matrix(rnorm(2000),nrow=40)) +
  WColorBarV(1:20, cmp=CMPar(), continuous=FALSE, RightOf())
```

row.cluster	<i>row cluster a matrix</i>
-------------	-----------------------------

Description

row cluster a matrix

Usage

```
row.cluster(mat, ..., hc.method = "ward.D2", dist.method = "euclidean")
```

Arguments

- mat input matrix
- ... extra color bars or matrix that needs row reordered.
- hc.method method to use in hclust
- dist.method method to use in dist

Value

a list of clustered row, column and matrix

Examples

```
WHeatmap(row.cluster(matrix(rnorm(100),nrow=10))$mat)
```

ScaleGroup	<i>Scale group</i>
------------	--------------------

Description

Scale group to incorporate text on margins

Usage

ScaleGroup(group.obj)

Arguments

group.obj group object that needs to be scaled

Value

scaled group obj

ToAffine	<i>Convert from absolute coordinates to affine coordinates</i>
----------	--

Description

Convert from absolute coordinates to affine coordinates

Usage

ToAffine(dm, dm.sys)

Arguments

dm dimension on the same coordinate system as the affine system (absolute coordinates)
dm.sys dimension of the affine system

Value

dimension on affine coordinates (relative coordinates)

TopLeftOf	<i>Top left of</i>
-----------	--------------------

Description

Place a new object to the top left corner of another.

Usage

```
TopLeftOf(x = NULL, just = c("right", "bottom"), v.pad = 0, h.pad = 0)
```

Arguments

x	target object, either a name, a object or NULL which refers to the last plotting object
just	the part from the new object that should be attached to
v.pad	vertical translational padding [0.0]
h.pad	horizontal translational padding [0.0]

Value

a WDimGenerator

Examples

```
WHeatmap(matrix(rnorm(2000),nrow=40)) +
  WHeatmap(matrix(c(rnorm(100)+1,rnorm(100)), nrow=10),
    cmp=CMPar(brewer.name = 'RdGy'), TopLeftOf(just=c('right','bottom'))))

WHeatmap(matrix(rnorm(2000),nrow=40)) +
  WHeatmap(matrix(c(rnorm(100)+1,rnorm(100)), nrow=10),
    cmp=CMPar(brewer.name = 'RdGy'), TopLeftOf(just=c('right','top'))))

WHeatmap(matrix(rnorm(2000),nrow=40)) +
  WHeatmap(matrix(c(rnorm(100)+1,rnorm(100)), nrow=10),
    cmp=CMPar(brewer.name = 'RdGy'), TopLeftOf(just=c('left','top'))))
```

TopOf	<i>Top of</i>
-------	---------------

Description

Generate dimension top of another object. Both the returned closure and the dimension it produces carry 'placement = "north"', which: * lets 'WColorBarH(..., label.use.data = TRUE)' default 'xticklabel.side = 't'' so in-situ labels point UPWARD (away from the heatmap body); and * at draw time, lets the sibling-aware relayout shift the new object upward by the predecessor's northward label overhang.

Usage

```
TopOf(  
  x = NULL,  
  height = NULL,  
  pad = 0.01,  
  min.ratio = 0.02,  
  h.aln = NULL,  
  v.scale = NULL,  
  v.scale.proportional = FALSE  
)
```

Arguments

- x an object with dimension
- height the height of the new object (when NULL, set to proportional to data)
- pad padding between the target and current
- min.ratio minimum ratio of dimensions when auto-scale
- h.aln object for horizontal alignment (when NULL, set to x)
- v.scale object for vertical scaling (when NULL, set to x)
- v.scale.proportional when v.scale is provided, whether to make proportional to data

Value

a dimension generator on top of x (with ‘placement = "north"’)

Examples

```
WHeatmap(matrix(rnorm(2000),nrow=40)) +  
  WColorBarH(1:20, cmp=CMPar(), continuous=FALSE, TopOf())
```

TopRightOf	<i>Top right of</i>
------------	---------------------

Description

Place a new object to the top right corner of another.

Usage

```
TopRightOf(x = NULL, just = c("left", "bottom"), v.pad = 0, h.pad = 0)
```

Arguments

<code>x</code>	target object, either a name, a object or NULL which refers to the last plotting object
<code>just</code>	the part from the new object that should be attached to
<code>v.pad</code>	vertical translational padding [0.0]
<code>h.pad</code>	horizontal translational padding [0.0]

Value

a WDimGenerator

Examples

```
WHeatmap(matrix(rnorm(2000),nrow=40)) +
  WHeatmap(matrix(c(rnorm(100)+1,rnorm(100)), nrow=10),
    cmp=CMPar(brewer.name = 'RdGy'), TopRightOf(just=c('left','bottom'))))

WHeatmap(matrix(rnorm(2000),nrow=40)) +
  WHeatmap(matrix(c(rnorm(100)+1,rnorm(100)), nrow=10),
    cmp=CMPar(brewer.name = 'RdGy'), TopRightOf(just=c('right','top'))))

WHeatmap(matrix(rnorm(2000),nrow=40)) +
  WHeatmap(matrix(c(rnorm(100)+1,rnorm(100)), nrow=10),
    cmp=CMPar(brewer.name = 'RdGy'), TopRightOf(just=c('left','top'))))
```

WColorBarH

WColorBarH

Description

A horizontal color bar.

Usage

```
WColorBarH(
  data,
  ...,
  label = NULL,
  label.side = "r",
  label.fontsize = 12,
  label.pad = 1,
  label.space = 0.05,
  label.use.data = FALSE
)
```

Arguments

<code>data</code>	numeric vector
<code>...</code>	additional options to <code>[WHeatmap()]</code> ; may include <code>'dm'</code> (a <code>[TopOf()]</code> / <code>[Beneath()]</code> generator or hard <code>'WDim'</code>), and any tick-label overrides such as <code>'xticklabel.side'</code>
<code>label</code>	colorbar header label (drawn at <code>'label.side'</code>)
<code>label.side</code>	<code>l</code> (for left) or <code>r</code> (for right) – header position
<code>label.fontsize</code>	label font size
<code>label.pad</code>	gap between in-situ (<code>label.use.data</code>) labels and the bar, expressed in units of the bar's cross-dimension – the bar height for a horizontal bar (this function) / the bar width for a vertical bar. The default 1.0 therefore offsets labels by exactly one bar thickness.
<code>label.space</code>	when <code>label.use.data</code> , the space between labels
<code>label.use.data</code>	use data to show legend in situ

Details

Since 0.2.3, when `'label.use.data = TRUE'` and the bar is placed via a `[TopOf()]` / `[Beneath()]` generator, the in-situ tick-label direction defaults outward (`'TopOf'` -> labels go up; `'Beneath'` -> labels go down). Pass an explicit `'xticklabel.side'` via `'...'` to override.

Value

an object of class `WColorBarH`

Examples

```
WColorBarH(matrix(1:50))
```

WColorBarV

WColorBarV

Description

A vertical color bar.

Usage

```
WColorBarV(
  data,
  ...,
  label = NULL,
  label.side = "t",
  label.fontsize = 12,
  label.pad = 1,
  label.space = 0.05,
  label.use.data = FALSE
)
```

Arguments

data	numeric vector
...	additional options to [WHeatmap()]; may include 'dm' (a [RightOf()]/[LeftOf()] generator or hard 'WDim'), and any tick-label overrides such as 'yticklabel.side'
label	colorbar header label (drawn at 'label.side')
label.side	t (for top) or b (for bottom) – header position
label.fontsize	label font size
label.pad	gap between in-situ (label.use.data) labels and the bar, expressed in units of the bar's cross-dimension – the bar width for a vertical bar (this function) / the bar height for a horizontal bar. The default 1.0 therefore offsets labels by exactly one bar thickness.
label.space	when label.use.data, the space between labels
label.use.data	use data to show legend in situ

Details

Since 0.2.3, when 'label.use.data = TRUE' and the bar is placed via a [RightOf()]/[LeftOf()] generator (anything carrying a 'placement' attribute), the in-situ tick-label direction defaults outward ('RightOf' -> labels go right; 'LeftOf' -> labels go left). Pass an explicit 'yticklabel.side' via '...' to override.

Value

an object of class WColorBarV

Examples

```
WColorBarV(matrix(50:1))
```

WColumnBind	<i>column bind non-overlapping objects</i>
-------------	--

Description

column bind non-overlapping objects

Usage

```
WColumnBind(..., nr = NULL, nc = NULL)
```

Arguments

...	plotting objects
nr	number of rows
nc	number of columns

Value

an object of class WDim

Examples

```
WHeatmap(matrix(rnorm(2000),nrow=40),name='a') +
  WHeatmap(matrix(rnorm(30), nrow=3), RightOf(),name='b') +
  WColorBarH(1:10, TopOf(WColumnBind('a','b')))
```

WCustomize

Customize an existing plot

Description

Set per-side outer margins as a fraction of the figure dimension. Since wheatmap 0.2.3 these are a ****minimum floor****: at draw time ‘print.WGroup’ wraps the figure in a gtable whose edge cells are auto-sized to fit any outward-facing tick / colorbar / legend labels, and the auto value wins when it exceeds the floor. Pre-0.2.3 call sites that passed e.g. ‘mar.right = 0.25’ to make room for long labels still work; the override just becomes redundant when the auto sizing already provides enough room.

Usage

```
WCustomize(
  mar.left = NULL,
  mar.right = NULL,
  mar.top = NULL,
  mar.bottom = NULL,
  mar = NULL
)
```

Arguments

mar.left	left margin floor, fraction of device width [0.03]
mar.right	right margin floor, fraction of device width [0.03]
mar.top	top margin floor, fraction of device height [0.03]
mar.bottom	bottom margin floor, fraction of device height [0.03]
mar	same floor in all four directions [0.03]

Details

Margins are interpreted in NPC of the device width (‘mar.left’, ‘mar.right’) or height (‘mar.top’, ‘mar.bottom’). ‘mar = 0.05’ is a shorthand for all four.

Value

an object of class WCustomize

Examples

```
## Old "make room for the legend" pattern still works
WHeatmap(matrix(c('fred','frank','brad',
                  'frank','fred','frank'), ncol=2)) +
  WLegendV(NULL, RightOf(), label.fontsize = 20) +
  WCustomize(mar.right=0.1)

## Equivalent under 0.2.3+: the auto-margin already reserves room
WHeatmap(matrix(c('fred','frank','brad',
                  'frank','fred','frank'), ncol=2)) +
  WLegendV(NULL, RightOf(), label.fontsize = 20) +
  WCustomize()
```

WDendrogram

*WDendrogram class***Description**

WDendrogram class

Usage

```
WDendrogram(
  clust = NULL,
  dm = WDim(0, 0, 1, 1),
  name = "",
  facing = c("bottom", "top", "left", "right")
)
```

Arguments

clust	hclust object
dm	plotting dimension
name	name of the dendrogram plot
facing	direction of the dendrogram plot

Value

an object of class WDendrogram

Examples

```
WDendrogram(column.cluster(matrix(1:24,nrow=4))$column.clust)
```

WDim*class WDim*

Description

class WDim

Usage

```
WDim(  
  left = 0,  
  bottom = 0,  
  width = 1,  
  height = 1,  
  nr = 1,  
  nc = 1,  
  text.x = 0,  
  text.y = 0,  
  text.just = c("center", "center"),  
  column.split = NULL,  
  row.split = NULL  
)
```

Arguments

left	left coordinate
bottom	bottom coordinate
width	width
height	height
nr	number of row
nc	number of column
text.x	x anchor for text
text.y	y anchor for text
text.just	just for text
column.split	a list of WDim objects for column split
row.split	a list of WDim objects for row split

Value

a WDim object

WGG	<i>WGG object form ggplot with coordinates</i>
-----	--

Description

WGG object form ggplot with coordinates

Usage

```
WGG(ggobj, dm = NULL, name = "")
```

Arguments

ggobj	ggplot plotting object
dm	dimension
name	name

Value

WGG object

WGrob	<i>WGrob object plot from a gList of grob objects</i>
-------	---

Description

WGrob object plot from a gList of grob objects

Usage

```
WGrob(glist, dm = NULL, name = "")
```

Arguments

glist	gList object
dm	dimension
name	name

Value

WGrob object

WGroup*Construct a WGroup*

Description

Construct a WGroup

Usage

```
WGroup(  
  ...,  
  name = "",  
  group.dm = NULL,  
  group.from.member = FALSE,  
  mar = WMar(),  
  affine = FALSE,  
  nr = NULL,  
  nc = NULL  
)
```

Arguments

...	plotting objects to be grouped
name	name of the group
group.dm	group dimension, by default use the dm of the merge of members
group.from.member	group merged from member coordinates (require affine == FALSE), the supplied group.dm is ignored
mar	a WMar object
affine	whether the group members are on affine coordinates already
nr	number of rows
nc	number of columns

Value

a WGroup object

WHeatmap

WHeatmap object

Description

Create a heatmap

Usage

```
WHeatmap(
  data = NULL,
  dm = NULL,
  name = "",
  continuous = NULL,
  cmp = NULL,
  cm = NULL,
  xticklabels = NULL,
  xticklabels.n = NULL,
  xticklabel.side = "b",
  xticklabel.fontsize = 12,
  xticklabel.rotat = 90,
  xticklabel.pad = 0.005,
  xticklabel.space = 0.05,
  xticklabel.use.data = FALSE,
  yticklabels = NULL,
  yticklabels.n = NULL,
  yticklabel.side = "l",
  yticklabel.fontsize = 12,
  yticklabel.rotat = 0,
  yticklabel.pad = 0.005,
  yticklabel.space = 0.05,
  yticklabel.use.data = FALSE,
  sub.name = NULL,
  bbox = FALSE,
  use_raster = FALSE,
  raster_device = NULL,
  raster_quality = 2,
  gp = NULL
)
```

Arguments

data	data matrix
dm	plotting dimension (a WDim or a WDimGenerator object)
name	name of the plot
continuous	whether the data should be treated as continuous or discrete

<code>cmp</code>	a CMPar object, for tuning color mapping parameters
<code>cm</code>	a given color map
<code>xticklabels</code>	to plot xtick labels, one may supply characters to plot just a subset of xtick labels
<code>xticklabels.n</code>	number of xtick labels to plot (resample for aesthetics by default)
<code>xticklabel.side</code>	xticklabel side (t or b)
<code>xticklabel.fontsize</code>	xticklabel font size
<code>xticklabel.rotat</code>	xticklabel rotation
<code>xticklabel.pad</code>	padding between xticklabel and x-axis
<code>xticklabel.space</code>	xticklabel space
<code>xticklabel.use.data</code>	use data to label x-axis (most likely used by colorbar)
<code>yticklabels</code>	to plot ytick labels, one may supply characters to plot just a subset of ytick labels
<code>yticklabels.n</code>	number of ytick labels to plot (resample for aesthetics by default)
<code>yticklabel.side</code>	yticklabel side (l or r)
<code>yticklabel.fontsize</code>	yticklabel font size
<code>yticklabel.rotat</code>	yticklabel rotation
<code>yticklabel.pad</code>	padding between yticklabel and y-axis
<code>yticklabel.space</code>	yticklabel space
<code>yticklabel.use.data</code>	use data to label y-axis (most likely used by colorbar)
<code>sub.name</code>	subclass name
<code>bbox</code>	whether to plot the boundary box (useful with white matrix elements)
<code>use_raster</code>	whether to render the heatmap body as a raster image using <code>grid.raster()</code> . This reduces file size and improves performance for large matrices. Default is FALSE.
<code>raster_device</code>	the off-screen graphics device for rasterization. Use "png" to render via a temp PNG file (requires the png package), or NULL (default) to construct the raster directly from the color matrix.
<code>raster_quality</code>	a scaling factor for the raster resolution when <code>raster_device</code> is set. Values > 1 increase resolution. Default is 2.
<code>gp</code>	a list of graphical parameters

Value

one or a list of heatmaps (depends on whether dimension is split)

Examples

```
WHeatmap(matrix(1:10, nrow=2), cmp=CMPar(brewer.name='Greens'))

WHeatmap(matrix(1:12,nrow=2), cmp=CMPar(brewer.name='Greens'), name='a') +
  WHeatmap(matrix(1:6,nrow=1), Beneath(pad=0.05), cmp=CMPar(brewer.name='Set2'), name='b') +
  WHeatmap(matrix(c(1:30,30:1),nrow=5), Beneath(pad=0.05), 'c', cmp=CMPar(cmap='jet')) +
  WHeatmap(matrix(1:24,nrow=4), RightOf('c'), 'd', cmp=CMPar(brewer.name='Set1')) +
  WLegendV('c', LeftOf('c', pad=0.01), yticklabel.side='l') +
  WLegendV('b', RightOf('b', width=0.1)) +
  WLegendV('a', RightOf('a')) +
  WHeatmap(matrix(1:100, nrow=10), RightOf('d'), cmp=CMPar(brewer.name='RdYlGn')) +
  WColorBarH(matrix(5:1), TopOf(), cmp=CMPar(colorsname = 'diverge_hcl')) +
  WColorBarH(matrix(50:1), TopOf(), cmp=CMPar(colorsname = 'terrain_hcl')) +
  WColorBarH(matrix(1:8), TopOf(), cmp=CMPar(colorsname = 'sequential_hcl')) +
  WColorBarH(matrix(1:8), TopOf(), cmp=CMPar(brewer.name = 'YlOrRd'))

## One could use %>% too, in combination with magrittr's add function
## Not run:
library(magrittr)
WColorBarH(1:10) %>% add(WColorBarV(rep(c('black','red','blue'),3), RightOf()))

## End(Not run)
```

WLabel

construct a WLabel

Description

construct a WLabel

Usage

```
WLabel(
  x = NULL,
  dm = WDim(),
  name = "",
  fontsize = 12,
  rot = 0,
  color = "black"
)
```

Arguments

x	text to be labeled
dm	position
name	name
fontsize	font size

rot	rotation
color	color of the label

Value

a WLabel object

Examples

```
WHeatmap(matrix(rnorm(2000),nrow=40)) + WLabel("This is a label.", RightOf(), rot=-90)
```

WLegendH

WLegendH

Description

a horizontal legend

Usage

```
WLegendH(
  x = NULL,
  dm = NULL,
  name = "",
  n.stops = 20,
  n.text = 5,
  label.fontsize = 12,
  width = 0.02,
  height = 0.05,
  decreasing = TRUE,
  ...
)
```

Arguments

x	a name or a plotting object, if NULL use the last plotting object
dm	position
name	name of the plotted legend
n.stops	number of stops in computing continuous legend
n.text	number of text labels in continuous legend
label.fontsize	label font size
width	width of each unit in plotted legend
height	height of each unit in plotted legend
decreasing	reversed color map
...	additional options to WHeatmap

Value

an object of class WLegendH

Examples

```
WHeatmap(matrix(1:4,nrow=2))+WLegendH(NULL, Beneath())
```

WLegendV

WLegendV

Description

a vertical legend

Usage

```
WLegendV(
  x = NULL,
  dm = NULL,
  name = "",
  n.stops = 20,
  n.text = 5,
  label.fontsize = 12,
  width = 0.05,
  height = 0.02,
  decreasing = FALSE,
  ...
)
```

Arguments

x	a name or a plotting object, if NULL use the last plotting object
dm	position
name	name of the plotted legend
n.stops	number of stops in computing continuous legend
n.text	number of text labels in continuous legend
label.fontsize	label font size
width	width of each unit in plotted legend
height	height of each unit in plotted legend
decreasing	reversed color map
...	additional options to WHeatmap

Value

an object of class WLegendV

Examples

```
WHeatmap(matrix(1:4,nrow=2))+WLegendV(NULL, RightOf())
```

WMatrix	<i>plot multiple figures in a matrix</i>
---------	--

Description

This function can take WObject, or gg (from ggplot) since the coordinates are not set, gg can be converted to WGG

Usage

```
WMatrix(objs, ncols = 1)
```

Arguments

objs	a list of plotting objects either WObject or gg
ncols	number of columns

Value

WGroup

WObject	<i>Construct a WObject</i>
---------	----------------------------

Description

Construct a WObject

Usage

```
WObject(dm = NULL, name = "")
```

Arguments

dm	position
name	name

Value

a WObject

WPosition	<i>place an arbitrary position w.r.t a subplot</i>
-----------	--

Description

place an arbitrary position w.r.t a subplot

Usage

```
WPosition(  
  anchor.x,  
  anchor.y,  
  x = NULL,  
  just = c("left", "bottom"),  
  data.coord = FALSE  
)
```

Arguments

anchor.x	x coordinates
anchor.y	y coordinates
x	plotting object to anchor
just	adjustment of new plot
data.coord	whether the coordinates is in term of data

Value

a WDimGenerator object

Examples

```
WHeatmap(matrix(rnorm(2000),nrow=40)) +  
  WHeatmap(matrix(c(rnorm(100)+1,rnorm(100)), nrow=10),  
    cmp=CMPar(brewer.name = 'RdGy'),  
    WPosition(0.1,0.1,just=c('left','top')))
```

WRect	<i>construct a WRect</i>
-------	--------------------------

Description

construct a WRect

Usage

```
WRect(
  obj = NULL,
  x.span = NULL,
  y.span = NULL,
  color = "black",
  lwd = 3,
  fill = NA,
  name = ""
)
```

Arguments

obj	a plotting object or its name
x.span	x-axis/horizontal span (e.g., c(2,4))
y.span	y-axis/vertical span (e.g., c(5,9))
color	edge color
lwd	edge width
fill	fill color
name	name

Value

a WRect object

WRowBind	<i>row bind non-overlapping objects</i>
----------	---

Description

row bind non-overlapping objects

Usage

```
WRowBind(..., nr = NULL, nc = NULL)
```

Arguments

<code>...</code>	plotting objects
<code>nr</code>	number of rows
<code>nc</code>	number of columns

Value

an object of class `WDim`

Examples

```
WHeatmap(matrix(rnorm(2000),nrow=40),name='a') +  
  WHeatmap(matrix(rnorm(30), nrow=3), Beneath(),name='b') +  
  WColorBarV(1:10, LeftOf(WRowBind('a','b')))
```

Index

`+.WObject`, [3](#)
`[.WGroup`, [3](#)

`AddWGroup`, [4](#)

`Beneath`, [4](#)
`both.cluster`, [5](#)
`BottomLeftOf`, [6](#)
`BottomRightOf`, [7](#)

`CalcTextBounding`, [7](#)
`CalcTextBounding.WHeatmap`, [8](#)
`CMPar`, [9](#)
`ColorMap`, [10](#)
`column.cluster`, [11](#)

`FromAffine`, [11](#)

`getdim`, [12](#)
`grid.dendrogram`, [12](#)
`GroupCheckNameUnique`, [13](#)
`GroupDeepGet`, [13](#)

`LeftOf`, [14](#)
`ly`, [15](#)

`MapToContinuousColors`, [15](#)
`MapToDiscreteColors`, [16](#)

`print.WDendrogram`, [16](#)
`print.WGenerator`, [17](#)
`print.WGG`, [17](#)
`print.WGrob`, [18](#)
`print.WGroup`, [18](#)
`print.WHeatmap`, [19](#)
`print.WLabel`, [20](#)
`print.WRect`, [20](#)

`Resolve`, [21](#)
`RightOf`, [21](#)
`row.cluster`, [22](#)

`ScaleGroup`, [23](#)

`ToAffine`, [23](#)
`TopLeftOf`, [24](#)
`TopOf`, [24](#)
`TopRightOf`, [25](#)

`WColorBarH`, [26](#)
`WColorBarV`, [27](#)
`WColumnBind`, [28](#)
`WCustomize`, [29](#)
`WDendrogram`, [30](#)
`WDim`, [31](#)
`WGG`, [32](#)
`WGrob`, [32](#)
`WGroup`, [33](#)
`WHeatmap`, [34](#)
`WLabel`, [36](#)
`WLegendH`, [37](#)
`WLegendV`, [38](#)
`WMatrix`, [39](#)
`WObject`, [39](#)
`WPosition`, [40](#)
`WRect`, [41](#)
`WRowBind`, [41](#)